



Profile Polymer UV Wax

Liquid Protection



Product Description

Profile Polymer UV Wax is a high performance polymeric wax specially developed for ultimate gloss and water resistance as well as provide protection against UV rays. It is extremely fast and easy to use by hand or machine, and is sprayable to make it easier to apply to surfaces, using either a small hand spray bottle or pump spray system. It is highly resistant to drying out and can be polished off easily to leave a durable high gloss on most surfaces.

Product Information

Size	Code	Ctn Qty
1 ltr	PRW101	6

Key Benefits

• Fast	Quick and easy to use making short work of large surfaces such as on boats, caravans, trucks and planes
• Superb Finish	Delivers a high gloss finish of excellent evenness and clarity even on blacks and dark colours
• Protection	Highly water resistant providing a durable protective coating repelling many common contaminants, and contains UV inhibitors
• Easy Application	Can be applied by hand or machine under most conditions and is resistant to drying
• Sprayable	Low viscosity sprayable formulation for ultra fast application



Far Simpler... Far Better...

+44 1920 465 041 | enquiries@farecla.com | www.farecla.com



Use With

Machine Application




G Mop Lambs Wool Pad
GML301 (3" / 75mm)
GML601 (6" / 150mm)
GML801 (8" / 200mm)



G Mop Finishing Foam
GMF301 (3" / 75mm)
GMF601 (6" / 150mm)
GMF801 (8" / 200mm)




G Mop Flexible Back Plate for 6" Pads
GMB146 (14mm thread)
GMB586 (5/8" thread)
GMB166 (16mm thread)



G Mop Flexible Back Plate for 8" Pads
GMB814 (14mm thread)
GMB858 (5/8" thread)
GMB816 (16mm thread)

Hand Application



Farécla Finishing Cloth
FC-3 (3 x cloths)

Spray Application




Water Spray Bottle
WSB (600ml)


How To Use




Shake the bottle well before use




Dispense a small quantity of the product onto the surface or pad



Spread then polish at 1000 to 1500rpm



Repeat for a greater gloss finish and protection



Wipe clean with a Finishing Cloth

Technical Information

Appearance: **Pink coloured liquid**
 Viscosity: **Low / medium viscosity**
 VOC Content: **131g/L**
 Relative Density: **0.960**
 pH: **7 (approx.)**
 Types of Surface: **Any painted, Industrial Surface**

Additional Information

Clean applicators before and after use with a Spurring Brush to prevent dried product damaging the surface being worked on.



Spurring Brush
1090005

